

1.1

Date of compilation: 05/10/2021

Product identifier:

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

### RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING



Revised: 28/02/2022

Version: 2 (Replaced 1)

**RENOLIT ALKORPLUS VOGUE - SEAM FINISH** 

# 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER Other means of identification: Non-applicable 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Multiuse adhesive. For professional user only. Uses advised against: All uses not specified in this section or in section 7.3 1.3 Details of the supplier of the safety data sheet: RENOLIT IBERICA SA Ctra. del Montnegre, s/n 08470 Sant Celoni - Barcelona - España Phone.: +34 938484000 - Fax: +34 938675936 piscinas@renolit.com http://renolit.com/swimmingpool 1.4 Emergency telephone number: +44 1235 239 670 SECTION 2: HAZARDS IDENTIFICATION 2.1 Classification of the substance or mixture: This product contains crystalline silica but due to its liquid state does not require classification (STOT RE) CLP Regulation (EC) No 1272/2008: Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008. Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336 2.2 Label elements: CLP Regulation (EC) No 1272/2008: Danger Hazard statements: Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness. Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively Supplementary information: EUH066: Repeated exposure may cause skin dryness or cracking. Substances that contribute to the classification Butanone (CAS: 78-93-3) Acute Toxicity Estimate (ATE mix):



### **RENOLIT ALKORPLUS VOGUE - SEAM FINISH** 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 2: HAZARDS IDENTIFICATION (continued)

19,8 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

UFI: U600-W0NR-3003-4TTE

#### 23 Other hazards:

Product fails to meet PBT/vPvB criteria

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture composed of pigments and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification			
	78-93-3 201-159-0	Butanone 1 ATP CLP00				
Index: REACH:	606-002-00-3 01-2119457290-43- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	70 - <85 %		
	108-10-1	4-methylpentan-2-one	ATP CLP00			
EC: 203-550-1 Index: 606-004-00-4 REACH: 01-2119473980-30- XXXX		Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH066 - Danger	1 - <5 %		
CAS: 7631-86-9 EC: 231-545-4 Index: Non-applicable REACH: 01-2119379499-16- XXXX		Silicon dioxide (1 % <	RCS < 10 %) 1 Self-classified			
		Regulation 1272/2008	STOT RE 2: H373 - Warning	1 - <2,5 %		
	112-34-5	2-(2-butoxyethoxy)eth	anol <sup>2</sup> ATP CLP00			
	603-096-00-8 01-2119475104-44-	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	0,01 - <0,05 %		
	533-00-6 208-551-0	Barium dibenzoate 2	Self-classified			
Index: REACH:	056-002-00-7 01-2120769909-30- XXXX	Regulation 1272/2008	Acute Tox. 3: H301; Acute Tox. 4: H332; Eye Dam. 1: H318 - Danger	0,001 - <0,01 %		
	108-95-2 203-632-7	phenol 2	ATP CLP00			
Index: REACH:	604-001-00-2 01-2119471329-32- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: 🛞 🐼 🔇	0,001 - <0,005 %		

□<sup>1</sup>□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 □<sup>2</sup>□ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

# SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance. By skin contact:



### RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO ).

#### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:



# RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

22 Version: 2 (Replaced 1)

# SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

#### A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits			
Butanone		IOELV (8h)	200 ppm	600 mg/m <sup>3</sup>	
CAS: 78-93-3 EC: 201-159-0		IOELV (STEL)	300 ppm	900 mg/m <sup>3</sup>	
4-methylpentan-2-one		IOELV (8h)	20 ppm	83 mg/m <sup>3</sup>	
CAS: 108-10-1 EC: 203-550-1		IOELV (STEL)	50 ppm	208 mg/m <sup>3</sup>	
Silicon dioxide (1 % < RCS < 10 %)		IOELV (8h)		0,1 mg/m <sup>3</sup>	
CAS: 7631-86-9 EC: 231-545-4		IOELV (STEL)			
2-(2-butoxyethoxy)ethanol		IOELV (8h)	10 ppm	67,5 mg/m <sup>3</sup>	
CAS: 112-34-5 EC: 203-961-6		IOELV (STEL)	15 ppm	101,2 mg/m <sup>3</sup>	
Barium dibenzoate		IOELV (8h)		0,5 mg/m <sup>3</sup>	
CAS: 533-00-6 EC: 208-551-0		IOELV (STEL)			
phenol		IOELV (8h)	2 ppm	8 mg/m <sup>3</sup>	
CAS: 108-95-2 EC: 203-632-7		IOELV (STEL)	4 ppm	16 mg/m <sup>3</sup>	



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

## RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

## DNEL (Workers):

		Short e	exposure	Long exposure	
Identification	Identification			Systemic	Local
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m³	Non-applicable
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	11,8 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	208 mg/m <sup>3</sup>	208 mg/m <sup>3</sup>	83 mg/m³	83 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m <sup>3</sup>	67,5 mg/m³	67,5 mg/m³
Barium dibenzoate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 533-00-6	Dermal	Non-applicable	Non-applicable	31,25 mg/kg	Non-applicable
EC: 208-551-0	Inhalation	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>	Non-applicable
phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable
EC: 203-632-7	Inhalation	Non-applicable	16 mg/m <sup>3</sup>	8 mg/m³	Non-applicable

# DNEL (General population):

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m <sup>3</sup>	Non-applicable
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	155,2 mg/m <sup>3</sup>	155,2 mg/m <sup>3</sup>	14,7 mg/m <sup>3</sup>	14,7 mg/m <sup>3</sup>
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	60,7 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>	40,5 mg/m <sup>3</sup>
Barium dibenzoate	Oral	Non-applicable	Non-applicable	3,21 mg/kg	Non-applicable
CAS: 533-00-6	Dermal	Non-applicable	Non-applicable	15,63 mg/kg	Non-applicable
EC: 208-551-0	Inhalation	Non-applicable	Non-applicable	2,79 mg/m³	Non-applicable
phenol	Oral	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
EC: 203-632-7	Inhalation	Non-applicable	Non-applicable	1,32 mg/m <sup>3</sup>	Non-applicable

PNEC:

Identification				
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
4-methylpentan-2-one	STP	27,5 mg/L	Fresh water	0,6 mg/L
CAS: 108-10-1	Soil	1,3 mg/kg	Marine water	0,06 mg/L
EC: 203-550-1	Intermittent	1,5 mg/L	Sediment (Fresh water)	8,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,83 mg/kg
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1,1 mg/L
CAS: 112-34-5	Soil	0,32 mg/kg	Marine water	0,11 mg/L
EC: 203-961-6	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg



## RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Barium dibenzoate	STP	Non-applicable	Fresh water	0,3026 mg/L
CAS: 533-00-6	Soil	546,6 mg/kg	Marine water	0,5313 mg/L
EC: 208-551-0	Intermittent	Non-applicable	Sediment (Fresh water)	1578,9 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
phenol	STP	2,1 mg/L	Fresh water	0,008 mg/L
CAS: 108-95-2	Soil	0,136 mg/kg	Marine water	0,001 mg/L
EC: 203-632-7	Intermittent	0,031 mg/L	Sediment (Fresh water)	0,091 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg

# 8.2

### Exposure controls:

### A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.



This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

## RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021 Revised: 28/02/2022

Version: 2 (Replaced 1)

Emergency measure	Standards	Emergency measure	Standards
<b>*</b>	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	● + T	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D **Volatile organic compounds:** 

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	60 % weight
V.O.C. density at 25 °C:	543,6 kg/m³ (543,6 g/L)
Average carbon number:	4,11
Average molecular weight:	73,69 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Annoaranoa

Appearance:		
Physical state at 20 °C:	Liquid	
Appearance:	Thixotropic	
Colour:	According to the markings on the package	
Odour:	Characteristic	
Odour threshold:	Non-applicable *	
Volatility:		
Boiling point at atmospheric pressure:	60 ℃	
Vapour pressure at 25 °C:	9302 Pa	
Vapour pressure at 50 °C:	36000 Pa (36 kPa)	
Evaporation rate at 25 °C:	Non-applicable *	
Product description:		
Density at 25 °C:	906 kg/m³ (ASTM D 2879-86)	
Relative density at 25 °C:	0,906	
Dynamic viscosity at 25 °C:	2500 cP	
Kinematic viscosity at 25 °C:	Non-applicable *	
Kinematic viscosity at 40 °C:	>1500 cSt	
Concentration:	Non-applicable *	
pH:	Non-applicable *	
Vapour density at 25 °C:	Non-applicable *	
Partition coefficient n-octanol/water 25 °C:	Non-applicable *	
Solubility in water at 25 °C:		
Solubility properties:	Insoluble in water, soluble in organic solvents	
Decomposition temperature:	Non-applicable *	
Melting point/freezing point:	Non-applicable *	
Explosive properties:	Non-applicable *	
*Not relevant due to the nature of the product, not providing	information property of its hazards.	



### RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of c	compilation: 05/10/2021	Revised: 28/02/2022	Version: 2 (Replaced 1)	
SECT	TION 9: PHYSICAL AND	CHEMICAL PROPER	TIES (continued)	
	Oxidising properties:		Non-applicable *	
	Flammability:			
	Flash Point:		-17 °C	
	Heat of combustion:		Non-applicable *	
	Flammability (solid, gas):		Non-applicable *	
	Autoignition temperature:		404 °C	
	Lower flammability limit:		1,8 % Volume	
	Upper flammability limit:		13 % Volume	
	Explosive:			
	Lower explosive limit:		Non-applicable *	
	Upper explosive limit:		Non-applicable *	
9.2	Other information:			
	Surface tension at 25 °C:		Non-applicable *	
	Refraction index:		Non-applicable *	
	*Not relevant due to the nature of	the product, not providing informa	tion property of its hazards.	

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Not applicable Risk of combustion Avoid direct impact Not applicable	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

# 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

# Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: A- Ingestion (acute effect):



# RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER

Date of compilation: 05/10/2021 Revised: 28/02/2022 Version: 2 (Replaced 1) SECTION 11: TOXICOLOGICAL INFORMATION (continued) Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3. Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3. B- Inhalation (acute effect): Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3. Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3. C- Contact with the skin and the eyes (acute effect): Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3. Contact with the eyes: Produces eye damage after contact. D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction): - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3. IARC: Polyvinyl chloride (3); 4-methylpentan-2-one (2B); Silicon dioxide (1 % < RCS < 10 %) (3); phenol (3) Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3. Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. E- Sensitizing effects: - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3. Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. F- Specific target organ toxicity (STOT) - single exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness. G- Specific target organ toxicity (STOT)-repeated exposure: Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3. Skin: Repeated exposure may cause skin dryness or cracking H- Aspiration hazard: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. Other information: Non-applicable Specific toxicology information on the substances: Identification Acute toxicity Genus LD50 oral 4000 mg/kg Rat Butanone 6400 mg/kg Rabbit LD50 dermal CAS: 78-93-3 EC: 201-159-0 LC50 inhalation 23,5 mg/L (4 h) Rat Silicon dioxide (1 % < RCS < 10 %) LD50 oral 5100 mg/kg Rat CAS: 7631-86-9 LD50 dermal 5100 mg/kg Rabbit LC50 inhalation EC: 231-545-4 Non-applicable LD50 oral 4-methylpentan-2-one 2080 mg/kg Non-applicable CAS: 108-10-1 LD50 dermal LC50 inhalation EC: 203-550-1 11 mg/L (4 h) (ATEi) LD50 oral 100 mg/kg phenol Rat

- CONTINUED ON NEXT PAGE -

LD50 dermal

LC50 inhalation

630 mg/kg

Non-applicable

CAS: 108-95-2

EC: 203-632-7

Rabbit



RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

### Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	195,57 mg/L (4 h) (Calculation method)	19,8 %

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
4-methylpentan-2-one	LC50	900 mg/L (48 h)	Leuciscus idus	Fish
CAS: 108-10-1	EC50	862 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-550-1	EC50	980 mg/L (48 h)	Scenedesmus subspicatus	Algae
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
phenol	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
CAS: 108-95-2	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-632-7	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae

## 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butanone	BOD5	2,03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %
4-methylpentan-2-one	BOD5	2,06 g O2/g	Concentration	100 mg/L
CAS: 108-10-1	COD	2,16 g O2/g	Period	14 days
EC: 203-550-1	BOD5/COD	0,95	% Biodegradable	84 %
2-(2-butoxyethoxy)ethanol	BOD5	0,25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2,08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0,12	% Biodegradable	92 %
phenol	BOD5	1,68 g O2/g	Concentration	100 mg/L
CAS: 108-95-2	COD	2,33 g O2/g	Period	14 days
EC: 203-632-7	BOD5/COD	0,72	% Biodegradable	85 %

# 12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential	
Butanone	E	BCF	3
CAS: 78-93-3	F	Pow Log	0.29
EC: 201-159-0	F	Potential	Low
4-methylpentan-2-one	E	BCF	2
CAS: 108-10-1	F	Pow Log	1.31
EC: 203-550-1	F	Potential	Low
2-(2-butoxyethoxy)ethanol	E	BCF	0.46
CAS: 112-34-5	F	Pow Log	0.56
EC: 203-961-6	F	Potential	Low
phenol	E	BCF	17
CAS: 108-95-2	F	Pow Log	1.48
EC: 203-632-7	F	Potential	Low





### RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER

Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

# SECTION 12: ECOLOGICAL INFORMATION (continued)

### 12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		itility
Butanone	Кос	30	Henry	5,77 Pa⋅m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
4-methylpentan-2-one	Кос	Non-applicable	Henry	Non-applicable
CAS: 108-10-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-550-1	Surface tension	2,35E-2 N/m (25 °C)	Moist soil	Non-applicable
2-(2-butoxyethoxy)ethanol	Кос	48	Henry	7,2E-9 Pa⋅m³/mol
CAS: 112-34-5	Conclusion	Very High	Dry soil	No
EC: 203-961-6	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No
phenol	Кос	50	Henry	2,2E-2 Pa⋅m³/mol
CAS: 108-95-2	Conclusion	Very High	Dry soil	Yes
EC: 203-632-7	Surface tension	1,847E-2 N/m (231,01 ℃)	Moist soil	Yes

# 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation





## RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER

Date of compilation: 05/10/2021	Revised: 28/02/2022 V	ersion: 2 (Replaced 1)
SECTION 14: TRANSPOR	T INFORMATION (continued)	
14.1 14.2 14.3 14.4 14.5 14.6 14.7	Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user Special regulations: Tunnel restriction code: Physico-Chemical properties: Limited quantities: Transport in bulk according to	UN1133 ADHESIVES containing flammable liquid 3 3 II No 640D D/E see section 9 5 L Non-applicable
Transaction	Annex II of Marpol and the IBC Code:	
Transport of dangerou With regard to IMDG 39		
14.1 14.2 14.3 14.4 14.5 14.6	UN proper shipping name: Transport hazard class(es): Labels: Packing group:	UN1133 ADHESIVES containing flammable liquid 3 3 II No Non-applicable F-E, S-D
14.7 Transport of dangerou	Annex II of Marpol and the IBC Code:	see section 9 5 L Non-applicable Non-applicable
With regard to IATA/ICA		
14.1 14.2 14.3 14.4 14.5 14.6	UN number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user Physico-Chemical properties:	UN1133 ADHESIVES containing flammable liquid 3 3 II No see section 9
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

# SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:
Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable
Seveso III:



# RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER



Date of compilation: 05/10/2021

Revised: 28/02/2022

Version: 2 (Replaced 1)

CTION 15: REGULATORY INFORMATION (continued)				
Section	Description	Lower-tier requirements	Upper-tier requirements	
P5c	FLAMMABLE LIQUIDS	5000	50000	
Limitations	to commercialisation and the use of certain dangerous substances and mixture	es (Annex XVII F	REACH, etc	
the general — metallic g — artificial s — "whooped — silly string — imitation d — horns for — decorativ — artificial c — stink born Without prej suppliers sh. visibly, legibl 'For professi Shall not be — ornamenta and ashtrays — tricks and — games for Occupationa Specific pro	a aerosols, excrement, parties, e flakes and foams, obwebs, bs. udice to the application of other Community provisions on the classification, packaging all ensure before the placing on the market that the packaging of aerosol dispensers r y and indelibly with: onal users only'. used in: al articles intended to produce light or colour effects by means of different phases, for s, jokes, one or more participants, or any article intended to be used as such, even with ornan al exposure to respirable crystalline silica must be controlled pursuant to Directive (EU positions in terms of protecting people or the environment:	g and labelling of eferred to above example in ornat nental aspects. ) 2019/130.	substances, is marked	
	ended to use the information included in this safety data sheet as a basis for conducti s in order to establish the necessary risk prevention measures for the handling, use, s ation:			

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### **SECTION 16: OTHER INFORMATION**

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

Removed substances

Zinc dibenzoate (553-72-0)

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation



### RENOLIT ALKORPLUS VOGUE - SEAM FINISH 81020001 VINTAGE, 81020002 URBAN, 81020003 SUMMER

te of compilation: 05/10/2021	Revised: 28/02/2022	Version: 2 (Replaced 1)
SECTION 16: OTHER INFOR	RMATION (continued)	
Acute Tox. 4: H332 - Harmi Eye Dam. 1: H318 - Causes Eye Irrit. 2: H319 - Causes Flam. Liq. 2: H225 - Highly Muta. 2: H341 - Suspected Skin Corr. 1B: H314 - Caus STOT RE 2: H373 - May ca	H331 - Toxic if swallowed, ful if inhaled. es serious eye damage. serious eye irritation. I flammable liquid and vapo of causing genetic defects ses severe skin burns and ause damage to organs the ause damage to organs the ause respiratory irritation.	ts. eye damage. rough prolonged or repeated exposure (Inhalation). rough prolonged or repeated exposure.
Classification procedure:	1	
Eye Irrit. 2: Calculation met STOT SE 3: Calculation me Flam. Lig. 2: Calculation me	ethod	
Advice related to training	( )	
Minimal training is recomm	ended in order to prevent	industrial risks for staff using this product and to facilitate their sheet, as well as the label on the product.
Principal bibliographical	sources:	
http://echa.europa.eu		
http://eur-lex.europa.eu		
Abbreviations and acrony	yms:	
ADR: European agreement IMDG: International maritim IATA: International Air Trans	ne dangerous goods code	nal carriage of dangerous goods by road
ICAO: International Civil Av	•	
COD: Chemical Oxygen De		
BOD5: 5day biochemical or	xygen demand	
BCF: Bioconcentration fact	or	
LD50: Lethal Dose 50	50	
LC50: Lethal Concentration		
EC50: Effective concentrati		
LogPOW: Octanolwater partition coefficient of		
	organic carbon	

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Version: 2 (Replaced 1)

Rely on it.

Revised: 28/02/2022