

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS **SEAM FINISH** 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 81024 - RENOLIT ALKORPLUS

SEAM FINISH

81024008 81024011

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Multiuse adhesive. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

> RENOLIT IBERICA SA Ctra. del Montnegre, s/n

08470 Sant Celoni - Barcelona - España Phone.: +34 938484000 - Fax: +34 938675936

piscinas@renolit.com

http://renolit.com/swimmingpool

Emergency telephone number: +44 1235 239 670 1.4

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture: 2.1

This product contains crystalline silica but due to its liquid state does not require classification (STOT RE)

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 2: Flammable liquids, Category 2, H225

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:





Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour. STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Substances that contribute to the classification

Butanone (CAS: 78-93-3)

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 1/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS **SEAM FINISH** 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Acute Toxicity Estimate (ATE mix):

19,8 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

UFI: 2300-D0YA-S00M-GG7C

Other hazards: 2.3

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of pigments and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS: EC:	78-93-3 201-159-0	Butanone □¹ □ ATP CLP00				
Index:	606-002-00-3 I: 01-2119457290-43- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	70 - <85 %		
CAS: EC:	108-10-1	4-methylpentan-2-one	□¹□ ATP CLP00			
Index:	203-550-1 606-004-00-4 I: 01-2119473980-30- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH066 - Danger	1 - <5 %		
CAS: EC:	7631-86-9 231-545-4	Silicon dioxide (1 % <	RCS < 10 %)□¹□ Self-classified			
Index:	Non-applicable I: 01-2119379499-16- XXXX	Regulation 1272/2008	STOT RE 2: H373 - Warning	1 - <2,5 %		
CAS: EC:	112-34-5 203-961-6	2-(2-butoxyethoxy)eth	nanol□²□ ATP CLP00			
Index:	603-096-00-8 1: 01-2119475104-44- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	0,01 - <0,05 %		
CAS:	533-00-6 208-551-0	Barium dibenzoate□²	Self-classified			
EC: Index: REACH	208-551-0 056-002-00-7 I: 01-2120769909-30- XXXX	Regulation 1272/2008	Acute Tox. 4: H302+H332 - Warning	0,001 - <0,01 %		
CAS: EC:	553-72-0 209-047-3	Zinc dibenzoate□³□	Self-classified			
Index:	Non-applicable I: 01-2120053849-43- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Eye Dam. 1: H318 - Danger	0,001 - <0,01 %		
CAS: EC:	108-95-2 203-632-7	phenol□²□	ATP CLP00			
Index:	203-632-7 604-001-00-2 I: 01-2119471329-32- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: H373 - Danger	0,001 - <0,005 %		

[□]¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 □²□ Substance with a Union workplace exposure limit □³□ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 2/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO□).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 3/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 8 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occ	Occupational exposure limits		
Butanone	IOELV (8h)	200 ppm	600 mg/m ³	
CAS: 78-93-3 EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m ³	
4-methylpentan-2-one	IOELV (8h)	20 ppm	83 mg/m³	
CAS: 108-10-1 EC: 203-550-1	IOELV (STEL)	50 ppm	208 mg/m ³	
Silicon dioxide (1 % < RCS < 10 %)	IOELV (8h)		0,1 mg/m ³	
CAS: 7631-86-9 EC: 231-545-4	IOELV (STEL)			
2-(2-butoxyethoxy)ethanol	IOELV (8h)	10 ppm	67,5 mg/m ³	
CAS: 112-34-5 EC: 203-961-6	IOELV (STEL)	15 ppm	101,2 mg/m ³	
Barium dibenzoate	IOELV (8h)		0,5 mg/m ³	

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occupational exposure limits		
CAS: 533-00-6	EC: 208-551-0	IOELV (STEL)		
phenol		IOELV (8h)	2 ppm	8 mg/m³
CAS: 108-95-2	EC: 203-632-7	IOELV (STEL)	4 ppm	16 mg/m³

DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m³	Non-applicable
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	11,8 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	208 mg/m³	208 mg/m³	83 mg/m³	83 mg/m³
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	101,2 mg/m³	67,5 mg/m³	67,5 mg/m³
Barium dibenzoate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 533-00-6	Dermal	Non-applicable	Non-applicable	31,25 mg/kg	Non-applicable
EC: 208-551-0	Inhalation	Non-applicable	Non-applicable	10 mg/m³	Non-applicable
Zinc dibenzoate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 553-72-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 209-047-3	Inhalation	Non-applicable	Non-applicable	5 mg/m³	Non-applicable
phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable
EC: 203-632-7	Inhalation	Non-applicable	16 mg/m³	8 mg/m³	Non-applicable

DNEL (General population):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable
4-methylpentan-2-one	Oral	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
CAS: 108-10-1	Dermal	Non-applicable	Non-applicable	4,2 mg/kg	Non-applicable
EC: 203-550-1	Inhalation	155,2 mg/m³	155,2 mg/m³	14,7 mg/m³	14,7 mg/m³
2-(2-butoxyethoxy)ethanol	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
CAS: 112-34-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
EC: 203-961-6	Inhalation	Non-applicable	60,7 mg/m³	40,5 mg/m³	40,5 mg/m ³
Barium dibenzoate	Oral	Non-applicable	Non-applicable	3,21 mg/kg	Non-applicable
CAS: 533-00-6	Dermal	Non-applicable	Non-applicable	15,63 mg/kg	Non-applicable
EC: 208-551-0	Inhalation	Non-applicable	Non-applicable	2,79 mg/m ³	Non-applicable
Zinc dibenzoate	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 553-72-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 209-047-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m³	Non-applicable
phenol	Oral	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
EC: 203-632-7	Inhalation	Non-applicable	Non-applicable	1,32 mg/m³	Non-applicable

PNEC:

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 5/14



This SDS is an English translation of Regulation (EU) n^{o} 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg
4-methylpentan-2-one	STP	27,5 mg/L	Fresh water	0,6 mg/L
CAS: 108-10-1	Soil	1,3 mg/kg	Marine water	0,06 mg/L
EC: 203-550-1	Intermittent	1,5 mg/L	Sediment (Fresh water)	8,27 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,83 mg/kg
2-(2-butoxyethoxy)ethanol	STP	200 mg/L	Fresh water	1,1 mg/L
CAS: 112-34-5	Soil	0,32 mg/kg	Marine water	0,11 mg/L
EC: 203-961-6	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg
Barium dibenzoate	STP	Non-applicable	Fresh water	0,3026 mg/L
CAS: 533-00-6	Soil	546,6 mg/kg	Marine water	0,5313 mg/L
EC: 208-551-0	Intermittent	Non-applicable	Sediment (Fresh water)	1578,9 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
phenol	STP	2,1 mg/L	Fresh water	0,008 mg/L
CAS: 108-95-2	Soil	0,136 mg/kg	Marine water	0,001 mg/L
EC: 203-632-7	Intermittent	0,031 mg/L	Sediment (Fresh water)	0,091 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 6/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
-3	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	⊣ (♦	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 60 % weight

V.O.C. density at 25 °C: 543,6 kg/m³ (543,6 g/L)

Average carbon number: 4,11

Average molecular weight: 73,69 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid
Appearance: Thixotropic

Colour: According to the markings on the package

Odour: Characteristic
Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 60 °C Vapour pressure at 25 °C: 9302 Pa

Vapour pressure at 50 °C: 36000 Pa (36 kPa)
Evaporation rate at 25 °C: Non-applicable *

Product description:

Density at 25 °C: 906 kg/m³ (ASTM D 2879-86)

Relative density at 25 °C: 0,906

Dynamic viscosity at 25 °C: 2500 cP

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 7/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Kinematic viscosity at 25 °C:

Kinematic viscosity at 40 °C:

Concentration:

PH:

Vapour density at 25 °C:

Non-applicable *

Solubility in water at 25 °C:

Solubility properties: Insoluble in water, soluble in organic solvents

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: -17 °C

Heat of combustion:

Flammability (solid, gas):

Non-applicable *

Non-applicable *

Autoignition temperature: 404 °C

Lower flammability limit: 1,8 % Volume
Upper flammability limit: 13 % Volume

Explosive:

Lower explosive limit:

Upper explosive limit:

Non-applicable *

Non-applicable *

9.2 Other information:

Surface tension at 25 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Polyvinyl chloride (3); 4-methylpentan-2-one (2B); Silicon dioxide (1 % < RCS < 10 %) (3); phenol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Non-applicable

Specific toxicology information on the substances:

Identification	Acu	te toxicity	Genus
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation	23,5 mg/L (4 h)	Rat
Silicon dioxide (1 % < RCS < 10 %)	LD50 oral	5100 mg/kg	Rat
CAS: 7631-86-9	LD50 dermal	5100 mg/kg	Rabbit
EC: 231-545-4	LC50 inhalation	Non-applicable	
4-methylpentan-2-one	LD50 oral	2080 mg/kg	
CAS: 108-10-1	LD50 dermal	Non-applicable	
EC: 203-550-1	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Zinc dibenzoate	LD50 oral	2565 mg/kg	Rat
CAS: 553-72-0	LD50 dermal	5500 mg/kg	Rabbit
EC: 209-047-3	LC50 inhalation	Non-applicable	
phenol	LD50 oral	100 mg/kg	Rat
CAS: 108-95-2	LD50 dermal	630 mg/kg	Rabbit
EC: 203-632-7	LC50 inhalation	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	195,57 mg/L (4 h) (Calculation method)	19,8 %

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
4-methylpentan-2-one	LC50	900 mg/L (48 h)	Leuciscus idus	Fish
CAS: 108-10-1	EC50	862 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-550-1	EC50	980 mg/L (48 h)	Scenedesmus subspicatus	Algae
2-(2-butoxyethoxy)ethanol	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 112-34-5	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-961-6	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
Zinc dibenzoate	LC50	0.78 mg/L (96 h)	Pimephales promelas	Fish
CAS: 553-72-0	EC50	1.2 mg/L (48 h)	Daphnia magna	Crustacean
EC: 209-047-3	EC50	0.2 mg/L (96 h)	Pseudokirchneriella subcapitata	Algae
phenol	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
CAS: 108-95-2	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-632-7	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butanone	BOD5 2,03 g O2/g		Concentration	Non-applicable
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 10/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Deg	radability	Biodegrada	bility
4-methylpentan-2-one	BOD5	2,06 g O2/g	Concentration	100 mg/L
CAS: 108-10-1	COD	2,16 g O2/g	Period	14 days
EC: 203-550-1	BOD5/COD	0,95	% Biodegradable	84 %
2-(2-butoxyethoxy)ethanol	BOD5	0,25 g O2/g	Concentration	100 mg/L
CAS: 112-34-5	COD	2,08 g O2/g	Period	28 days
EC: 203-961-6	BOD5/COD	0,12	% Biodegradable	92 %
phenol	BOD5	1,68 g O2/g	Concentration	100 mg/L
CAS: 108-95-2	COD	2,33 g O2/g	Period	14 days
EC: 203-632-7	BOD5/COD	0,72	% Biodegradable	85 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Butanone	BCF	3
CAS: 78-93-3	Pow Log	0.29
EC: 201-159-0	Potential	Low
4-methylpentan-2-one	BCF	2
CAS: 108-10-1	Pow Log	1.31
EC: 203-550-1	Potential	Low
2-(2-butoxyethoxy)ethanol	BCF	0.46
CAS: 112-34-5	Pow Log	0.56
EC: 203-961-6	Potential	Low
phenol	BCF	17
CAS: 108-95-2	Pow Log	1.48
EC: 203-632-7	Potential	Low

12.4 Mobility in soil:

Identification	Identification Absorption/desorption		Vola	tility
Butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
4-methylpentan-2-one	Koc	Non-applicable	Henry	Non-applicable
CAS: 108-10-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-550-1	Surface tension	2,35E-2 N/m (25 °C)	Moist soil	Non-applicable
2-(2-butoxyethoxy)ethanol	Koc	48	Henry	7,2E-9 Pa·m³/mol
CAS: 112-34-5	Conclusion	Very High	Dry soil	No
EC: 203-961-6	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No
Zinc dibenzoate	Koc	15.5	Henry	Non-applicable
CAS: 553-72-0	Conclusion	Very High	Dry soil	Non-applicable
EC: 209-047-3	Surface tension	Non-applicable	Moist soil	Non-applicable
phenol	Koc	50	Henry	2,2E-2 Pa·m³/mol
CAS: 108-95-2	Conclusion	Very High	Dry soil	Yes
EC: 203-632-7	Surface tension	1,847E-2 N/m (231,01 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 11/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

3

14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES containing flammable liquid

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

 14.5
 Environmental hazards:
 No

14.6 Special precautions for user

Special regulations: 640D Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according to Non-applicable Annex II of Marpol and the IBC

Code:

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES containing flammable liquid

14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: II
14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: Non-applicable
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **Transport in bulk according to** Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC

Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 12/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES containing flammable liquid

14.3 Transport hazard class(es): 3
Labels: 3

14.4Packing group:II14.5Environmental hazards:No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC

Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs.
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes.
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

- CONTINUED ON NEXT PAGE -

Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1) Page 13/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81024 - RENOLIT ALKORPLUS SEAM FINISH 81024008 81024011



Date of compilation: 25/02/2016 Revised: 12/02/2021 Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Muta. 2: H341 - Suspected of causing genetic defects.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.