

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 81045001-81045002 - RENOLIT ALKORGLUE

RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Neoprene-base contact adhesive. For professional user only. Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

RENOLIT IBERICA SA Ctra. del Montnegre, s/n

08470 Sant Celoni - Barcelona - España Phone: +34 938484000 - Fax: +34 938675936

piscinas@renolit.com

http://renolit.com/swimmingpool

1.4 Emergency telephone number: +44 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 2: Flammable liquids, Category 2, H225

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312: Call a POISON CENTER/doctor if you feel unwell.

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment.

Supplementary information:

EUH208: Contains Rosin. May produce an allergic reaction.

UFI: WJT0-HV3V-R31X-6UHT



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE





RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of polymers and resins in solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | | Chemical name/Classification | | Concentration | |
|-------------------------|---|-------------------------------|---|--|---------------|--|
| CAS: EC: | Non-applicable 926-605-8 | Hydrocarbons, C6-C7 | , isoalkanes, cyclics, <5% n-hexane □¹□ | Self-classified | | |
| Index: | Non-applicable : 01-2119486291-36- XXXX | Regulation 1272/2008 | Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger | | 25 - <50 % | |
| CAS: EC: | 141-78-6 | Ethyl acetate □¹□ | | ATP CLP00 | | |
| Index: | 205-500-4 607-022-00-5 H: 01-2119475103-46- XXXX | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | ♦ | 25 - <50 % | |
| CAS: | 25085-50-1 | 4-tert-butylphenol-for | maldehyde copolymer □¹□ | Self-classified | | |
| EC: Index: REACH: | 472-160-3 Non-applicable : 01-0000019790-66- XXXX | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning | <u>\tag{\tag{\tag{\tag{\tag{\tag{\tag{</u> | 2,5 - <10 % | |
| CAS: EC: | 123-86-4 204-658-1 607-025-00-1 d: 01-2119485493-29- XXXX | N-butyl acetate □¹□ ATP CLP00 | | | | |
| Index: | | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning | <u>(1)</u> | 5 - <10 % | |
| CAS: EC: | 8050-09-7 232-475-7 | Rosin□¹□ | | ATP CLP00 | | |
| Index: | 650-015-00-7 : 01-2119480418-32- XXXX | Regulation 1272/2008 | Skin Sens. 1: H317 - Warning | <u>(1)</u> | 0,1 - <1 % | |
| CAS: EC: | 50-00-0 200-001-8 | Formaldehyde □²□ | | ATP ATP06 | | |
| Index: | 200-001-8 605-001-00-5 H: 01-2119488953-20- XXXX | Regulation 1272/2008 | Acute Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger | | <0,1 % | |

[□]¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11) Page 2/14

[□]²□ Substance with a Union workplace exposure limit

^{**} Changes with regards to the previous version



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE



Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 4: FIRST AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO□).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11) Page 3/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE



Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|-----------------------------|------------------------------|---------|------------------------|
| Ethyl acetate | IOELV (8h) | 200 ppm | 734 mg/m³ |
| CAS: 141-78-6 EC: 205-500-4 | IOELV (STEL) | 400 ppm | 1468 mg/m³ |
| N-butyl acetate | IOELV (8h) | 50 ppm | 241 mg/m³ |
| CAS: 123-86-4 EC: 204-658-1 | IOELV (STEL) | 150 ppm | 723 mg/m³ |
| Formaldehyde | IOELV (8h) | 0,3 ppm | 0,37 mg/m ³ |
| CAS: 50-00-0 EC: 200-001-8 | IOELV (STEL) | 0,6 ppm | 0,74 mg/m³ |

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|--|------------|----------------|----------------|----------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: Non-applicable | Dermal | Non-applicable | Non-applicable | 13964 mg/kg | Non-applicable |
| EC: 926-605-8 | Inhalation | Non-applicable | Non-applicable | 5306 mg/m³ | Non-applicable |
| Ethyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 141-78-6 | Dermal | Non-applicable | Non-applicable | 63 mg/kg | Non-applicable |
| EC: 205-500-4 | Inhalation | 1468 mg/m³ | 1468 mg/m³ | 734 mg/m³ | 734 mg/m³ |



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | | Short e | xposure | Long e | xposure |
|-----------------|------------|----------------|----------------|----------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| N-butyl acetate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 123-86-4 | Dermal | 11 mg/kg | Non-applicable | 11 mg/kg | Non-applicable |
| EC: 204-658-1 | Inhalation | 600 mg/m³ | 600 mg/m³ | 300 mg/m³ | 300 mg/m³ |
| Rosin | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 8050-09-7 | Dermal | Non-applicable | Non-applicable | 2,131 mg/kg | Non-applicable |
| EC: 232-475-7 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 10 mg/m³ |
| Formaldehyde | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 50-00-0 | Dermal | Non-applicable | Non-applicable | 240 mg/kg | Non-applicable |
| EC: 200-001-8 | Inhalation | Non-applicable | 0,75 mg/m³ | 9 mg/m³ | 0,375 mg/m³ |

DNEL (General population):

| | Short exposure | | Long exposure | | |
|--|----------------|----------------|----------------|----------------|----------------|
| Identification | Systemic | Local | Systemic | Local | |
| Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane | Oral | Non-applicable | Non-applicable | 1301 mg/kg | Non-applicable |
| CAS: Non-applicable | Dermal | Non-applicable | Non-applicable | 1377 mg/kg | Non-applicable |
| EC: 926-605-8 | Inhalation | Non-applicable | Non-applicable | 1131 mg/m³ | Non-applicable |
| Ethyl acetate | Oral | Non-applicable | Non-applicable | 4,5 mg/kg | Non-applicable |
| CAS: 141-78-6 | Dermal | Non-applicable | Non-applicable | 37 mg/kg | Non-applicable |
| EC: 205-500-4 | Inhalation | 734 mg/m³ | 734 mg/m³ | 367 mg/m³ | 367 mg/m³ |
| N-butyl acetate | Oral | 2 mg/kg | Non-applicable | 2 mg/kg | Non-applicable |
| CAS: 123-86-4 | Dermal | 6 mg/kg | Non-applicable | 6 mg/kg | Non-applicable |
| EC: 204-658-1 | Inhalation | 300 mg/m³ | 300 mg/m³ | 35,7 mg/m³ | 35,7 mg/m³ |
| Rosin | Oral | Non-applicable | Non-applicable | 1,065 mg/kg | Non-applicable |
| CAS: 8050-09-7 | Dermal | Non-applicable | Non-applicable | 1,065 mg/kg | Non-applicable |
| EC: 232-475-7 | Inhalation | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| Formaldehyde | Oral | Non-applicable | Non-applicable | 4,1 mg/kg | Non-applicable |
| CAS: 50-00-0 | Dermal | Non-applicable | Non-applicable | 102 mg/kg | Non-applicable |
| EC: 200-001-8 | Inhalation | Non-applicable | Non-applicable | 3,2 mg/m³ | 0,1 mg/m³ |

PNEC:

| Identification | | | | |
|-----------------|--------------|----------------|-------------------------|-------------|
| Ethyl acetate | STP | 650 mg/L | Fresh water | 0,24 mg/L |
| CAS: 141-78-6 | Soil | 0,148 mg/kg | Marine water | 0,024 mg/L |
| EC: 205-500-4 | Intermittent | 1,65 mg/L | Sediment (Fresh water) | 1,15 mg/kg |
| | Oral | 0,2 g/kg | Sediment (Marine water) | 0,115 mg/kg |
| N-butyl acetate | STP | 35,6 mg/L | Fresh water | 0,18 mg/L |
| CAS: 123-86-4 | Soil | 0,09 mg/kg | Marine water | 0,018 mg/L |
| EC: 204-658-1 | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,098 mg/kg |
| Rosin | STP | 1000 mg/L | Fresh water | 0,002 mg/L |
| CAS: 8050-09-7 | Soil | 0 mg/kg | Marine water | 0 mg/L |
| EC: 232-475-7 | Intermittent | 0,016 mg/L | Sediment (Fresh water) | 0,007 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,001 mg/kg |
| ormaldehyde | STP | 0,19 mg/L | Fresh water | 0,44 mg/L |
| CAS: 50-00-0 | Soil | 0,2 mg/kg | Marine water | 0,44 mg/L |
| EC: 200-001-8 | Intermittent | 4,44 mg/L | Sediment (Fresh water) | 2,3 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 2,3 mg/kg |

8.2 Exposure controls:


A.- General security and hygiene measures in the work place

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

(!) (M)



Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-----------------------------------|-----------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours | CAT III | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|--|-----------|--------------|---|
| Mandatory hand protection | Protective gloves against minor risks | CATI | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018 |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|---|-----------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against splash/projections. | CATII | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------|---|-----------|--|---|
| Mandatory complete body protection | Antistatic and fireproof protective clothing | CAT III | EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018 | Limited protection against flames. |
| Mandatory foot protection | Safety footwear with antistatic and heat resistant properties | CAT III | EN ISO 13287:2013 EN ISO 20345:2011 | Replace boots at any sign of deterioration. |

F - Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | ⊢ | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower | | Eyewash stations | |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 74,89 % weight

V.O.C. density at 25 °C: 647,81 kg/m³ (647,81 g/L)

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11) Page 6/14

RENOLIT Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Average carbon number: 5,2

Average molecular weight: 88,32 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Solvent

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 81 °C
Vapour pressure at 25 °C: 5322 Pa

Vapour pressure at 50 °C: 15896,45 Pa (15,9 kPa)

Evaporation rate at 25 °C: Non-applicable *

Product description:

Density at 25 °C: 845 - 885 kg/m³

Relative density at 25 °C: 0,88

Dynamic viscosity at 25 °C:

Kinematic viscosity at 25 °C:

Kinematic viscosity at 25 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Vapour density at 25 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Partition coefficient n-octanol/water 25 °C: Non-applicable *

Solubility in water at 25 °C:

Solubility properties: Insoluble in water, soluble in organic solvents

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: -1 °C

Heat of combustion:

Non-applicable *

Flammability (solid, gas):

Non-applicable *

Autoignition temperature: 345 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11) Page 7/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 25 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| | Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|---|--------------------|------------------|-------------------------|---------------------|----------------|
| Г | Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE **RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE**



Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
- IARC: Formaldehyde (1); Polychloroprene (3); Talc (3); disulfiram (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | | A | Acute toxicity | |
|-----------------|--|-----------------|-----------------|--------|
| Ethyl acetate | | LD50 oral | 4100 mg/kg | Rat |
| CAS: 141-78-6 | | LD50 dermal | 20000 mg/kg | Rabbit |
| EC: 205-500-4 | | LC50 inhalation | Non-applicable | |
| N-butyl acetate | | LD50 oral | 12789 mg/kg | Rat |
| CAS: 123-86-4 | | LD50 dermal | 14112 mg/kg | Rabbit |
| EC: 204-658-1 | | LC50 inhalation | 23,4 mg/L (4 h) | Rat |
| Rosin | | LD50 oral | 4100 mg/kg | Rat |
| CAS: 8050-09-7 | | LD50 dermal | Non-applicable | |
| EC: 232-475-7 | | LC50 inhalation | Non-applicable | |
| Formaldehyde | | LD50 oral | 100 mg/kg | Rat |
| CAS: 50-00-0 | | LD50 dermal | 270 mg/kg | Rabbit |
| EC: 200-001-8 | | LC50 inhalation | 1,1 mg/L (4 h) | Rat |

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

| Identification | Acute toxicity | | Species | Genus |
|--|----------------|---------------------|---------|------------|
| Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane | LC50 | >1 - 10 mg/L (96 h) | | Fish |
| CAS: Non-applicable | EC50 | >1 - 10 mg/L (48 h) | | Crustacean |
| EC: 926-605-8 | EC50 | >1 - 10 mg/L (72 h) | | Algae |

^{**} Changes with regards to the previous version



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | | Acute toxicity | Species | Genus |
|---|------|------------------|---------------------------|------------|
| Ethyl acetate | LC50 | 230 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 141-78-6 | EC50 | 717 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 205-500-4 | EC50 | 3300 mg/L (48 h) | Scenedesmus subspicatus | Algae |
| 4-tert-butylphenol-formaldehyde copolymer | LC50 | 0.26 mg/L (96 h) | N/A | Fish |
| CAS: 25085-50-1 | EC50 | 1.4 mg/L (48 h) | N/A | Crustacean |
| EC: 472-160-3 | EC50 | Non-applicable | | |
| N-butyl acetate | LC50 | Non-applicable | | |
| CAS: 123-86-4 | EC50 | Non-applicable | | |
| EC: 204-658-1 | EC50 | 675 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Rosin | LC50 | 150 mg/L (96 h) | Brachydanio rerio | Fish |
| CAS: 8050-09-7 | EC50 | 238 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 232-475-7 | EC50 | 185 mg/L (72 h) | Selenastrum capricornutum | Algae |
| Formaldehyde | LC50 | 100 mg/L (96 h) | Lepomis macrochirus | Fish |
| CAS: 50-00-0 | EC50 | 42 mg/L (24 h) | Daphnia magna | Crustacean |
| EC: 200-001-8 | EC50 | Non-applicable | | |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradab | ability | |
|-----------------|---------------|----------------|-----------------|----------------|--|
| Ethyl acetate | BOD5 | 1,36 g O2/g | Concentration | 100 mg/L | |
| CAS: 141-78-6 | COD | 1,69 g O2/g | Period | 14 days | |
| EC: 205-500-4 | BOD5/COD | 0,8 | % Biodegradable | 83 % | |
| N-butyl acetate | BOD5 | Non-applicable | Concentration | Non-applicable | |
| CAS: 123-86-4 | COD | Non-applicable | Period | 5 days | |
| EC: 204-658-1 | BOD5/COD | Non-applicable | % Biodegradable | 84 % | |
| Rosin | BOD5 | Non-applicable | Concentration | Non-applicable | |
| CAS: 8050-09-7 | COD | Non-applicable | Period | 28 days | |
| EC: 232-475-7 | BOD5/COD | Non-applicable | % Biodegradable | 32 % | |
| Formaldehyde | BOD5 | Non-applicable | Concentration | 100 mg/L | |
| CAS: 50-00-0 | COD | Non-applicable | Period | 14 days | |
| EC: 200-001-8 | BOD5/COD | Non-applicable | % Biodegradable | 92 % | |

12.3 Bioaccumulative potential:

| Identification | Bioacc | Bioaccumulation potential | | |
|---|-----------|---------------------------|--|--|
| Ethyl acetate | BCF | 30 | | |
| CAS: 141-78-6 | Pow Log | 0.73 | | |
| EC: 205-500-4 | Potential | Moderate | | |
| 4-tert-butylphenol-formaldehyde copolymer | BCF | | | |
| CAS: 25085-50-1 | Pow Log | 4.67 | | |
| EC: 472-160-3 | Potential | | | |
| N-butyl acetate | BCF | 4 | | |
| CAS: 123-86-4 | Pow Log | 1.78 | | |
| EC: 204-658-1 | Potential | Low | | |
| Formaldehyde | BCF | 3 | | |
| CAS: 50-00-0 | Pow Log | 0.35 | | |
| EC: 200-001-8 | Potential | Low | | |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|----------------|-----------------------|----------------------|------------|-----------------|
| Ethyl acetate | Koc | 59 | Henry | 13,58 Pa·m³/mol |
| CAS: 141-78-6 | Conclusion | Very High | Dry soil | Yes |
| EC: 205-500-4 | Surface tension | 2,324E-2 N/m (25 °C) | Moist soil | Yes |

^{**} Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11) Page 10/14



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation







81045001-81045002 - RENOLIT ALKORGLUE **RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE**

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Absorption/desorption | | Volatility | |
|-----------------|-----------------------|----------------------|------------|----------------|
| N-butyl acetate | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 123-86-4 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 204-658-1 | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Non-applicable |
| Formaldehyde | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 50-00-0 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 200-001-8 | Surface tension | 1,416E-2 N/m (25 °C) | Moist soil | Non-applicable |

Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| C | Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|---|------|---|---|
| | | It is not possible to assign a specific code, as it depends on the intended use by the user | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

14.1 UN number: UN1133

UN proper shipping name: ADHESIVES containing flammable liquid 14.2

Transport hazard class(es): Labels 3 14.4 Packing group: Ш

14.5 Environmental hazards: Yes

14.6 Special precautions for user Special regulations:

640D Tunnel restriction code: D/F Physico-Chemical properties: see section 9

Limited quantities: 5 I

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

- CONTINUED ON NEXT PAGE -

Revised: 05/10/2021 Date of compilation: 18/06/2018 Version: 12 (Replaced 11) Page 11/14

Changes with regards to the previous version



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation





81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES containing flammable liquid

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

 14.5
 Marine pollutant:
 Yes

14.6 Special precautions for user

Special regulations:

EmS Codes:

Physico-Chemical properties:

Non-applicable
F-E, S-D
see section 9

Limited quantities: 5 L

Segregation group: Non-applicable

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:

14.1 UN number: UN1133

14.2 UN proper shipping name: ADHESIVES containing flammable liquid

14.3Transport hazard class(es):3Labels:314.4Packing group:II14.5Environmental hazards:Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according to Non-applicable

Annex II of Marpol and the IBC

Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Formaldehyde (Product-type 2, 3, 22)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| | Section | Description | Lower-tier requirements | Upper-tier requirements |
|---|---------|-----------------------|-------------------------|-------------------------|
| | P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |
| ſ | E2 | ENVIRONMENTAL HAZARDS | 200 | 500 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

- CONTINUED ON NEXT PAGE -

RENOLIT Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs.
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays.
- -tricks and jokes.
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 12):

- · New declared substances
 - 4-tert-butylphenol-formaldehyde copolymer (25085-50-1)

Texts of the legislative phrases mentioned in section 2:

- H225: Highly flammable liquid and vapour.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H411: Toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Rely on it

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018 Revised: 05/10/2021 Version: 12 (Replaced 11)

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aguatic Chronic 2: H411 - Toxic to aguatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 1B: H350 - May cause cancer.

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Muta. 2: H341 - Suspected of causing genetic defects.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation. storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.