



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** RENOLIT ALKORPLUS - PVC SEAM SEALER
81028-81029-81032-81034-81035-81037-81039-81049-81050-81054
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Multiuse adhesive. For professional user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
RENOLIT IBERICA SA
Ctra. del Montnegre, s/n
08470 Sant Celoni - Barcelona - España
Phone.: +34 938484000 - Fax: +34 938675936
piscinas@renolit.com
http://renolit.com/swimmingpool
- 1.4 Emergency telephone number:** +44 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
This product contains crystalline silica but due to its liquid state does not require classification (STOT RE)
- CLP Regulation (EC) No 1272/2008:**
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 2: Flammable liquids, Category 2, H225
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Carc. 2: H351 - Suspected of causing cancer.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH019: May form explosive peroxides.
EUH208: Contains Octabenzene. May produce an allergic reaction.

Substances that contribute to the classification

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 1/14



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 2: HAZARDS IDENTIFICATION (continued)

tetrahydrofuran (CAS: 109-99-9)

UFI: R110-Y0JQ-5002-R7N2

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of pigments and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 109-99-9 EC: 203-726-8 Index: 603-025-00-0 REACH: 01-2119444314-46-XXXX	tetrahydrofuran <input type="checkbox"/> ¹ <input type="checkbox"/> ATP ATP03	70 - <90 %
	Regulation 1272/2008 Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH019 - Danger	
CAS: 7631-86-9 EC: 231-545-4 Index: Non-applicable REACH: 01-2119379499-16-XXXX	Silicon dioxide (1 % < RCS < 10 %) <input type="checkbox"/> ¹ <input type="checkbox"/> Self-classified	1 - <2,5 %
	Regulation 1272/2008 STOT RE 2: H373 - Warning	
CAS: 1843-05-6 EC: 217-421-2 Index: Non-applicable REACH: 01-2119557833-30-XXXX	Octabenzene <input type="checkbox"/> ¹ <input type="checkbox"/> Self-classified	0,1 - <0,5 %
	Regulation 1272/2008 Skin Sens. 1B: H317 - Warning	
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	2-(2-butoxyethoxy)ethanol <input type="checkbox"/> ² <input type="checkbox"/> ATP CLP00	0,01 - <0,05 %
	Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	
CAS: 533-00-6 EC: 208-551-0 Index: 056-002-00-7 REACH: 01-21120769909-30-XXXX	Barium dibenzoate <input type="checkbox"/> ² <input type="checkbox"/> Self-classified	0,001 - <0,01 %
	Regulation 1272/2008 Acute Tox. 3: H301; Acute Tox. 4: H332; Eye Dam. 1: H318 - Danger	
CAS: 108-95-2 EC: 203-632-7 Index: 604-001-00-2 REACH: 01-2119471329-32-XXXX	phenol <input type="checkbox"/> ² <input type="checkbox"/> ATP CLP00	0,001 - <0,005 %
	Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: H373 - Danger	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

² Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 2/14



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050- 81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 4: FIRST AID MEASURES (continued)

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 3/14



Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)		
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	IOELV (8h)	50 ppm	150 mg/m ³
	IOELV (STEL)	100 ppm	300 mg/m ³
Silicon dioxide (1 % < RCS < 10 %) CAS: 7631-86-9 EC: 231-545-4	IOELV (8h)		0,1 mg/m ³
	IOELV (STEL)		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	IOELV (8h)	10 ppm	67,5 mg/m ³
	IOELV (STEL)	15 ppm	101,2 mg/m ³
Barium dibenzoate CAS: 533-00-6 EC: 208-551-0	IOELV (8h)		0,5 mg/m ³
	IOELV (STEL)		
phenol CAS: 108-95-2 EC: 203-632-7	IOELV (8h)	2 ppm	8 mg/m ³
	IOELV (STEL)	4 ppm	16 mg/m ³

DNEL (Workers):

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 4/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER
81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015 Revised: 28/02/2022 Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	12,6 mg/kg	Non-applicable
	Inhalation	96 mg/m ³	300 mg/m ³	72,4 mg/m ³	150 mg/m ³
Octabenzene CAS: 1843-05-6 EC: 217-421-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,88 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6,61 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³
Barium dibenzoate CAS: 533-00-6 EC: 208-551-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	31,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10 mg/m ³	Non-applicable
phenol CAS: 108-95-2 EC: 203-632-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable
	Inhalation	Non-applicable	16 mg/m ³	8 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Oral	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
	Inhalation	52 mg/m ³	150 mg/m ³	13 mg/m ³	75 mg/m ³
Octabenzene CAS: 1843-05-6 EC: 217-421-2	Oral	Non-applicable	Non-applicable	0,94 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,94 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,63 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
	Inhalation	Non-applicable	60,7 mg/m ³	40,5 mg/m ³	40,5 mg/m ³
Barium dibenzoate CAS: 533-00-6 EC: 208-551-0	Oral	Non-applicable	Non-applicable	3,21 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	15,63 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,79 mg/m ³	Non-applicable
phenol CAS: 108-95-2 EC: 203-632-7	Oral	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,32 mg/m ³	Non-applicable

PNEC:

Identification				
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	STP	4,6 mg/L	Fresh water	4,32 mg/L
	Soil	2,13 mg/kg	Marine water	0,432 mg/L
	Intermittent	21,6 mg/L	Sediment (Fresh water)	23,3 mg/kg
	Oral	0,067 g/kg	Sediment (Marine water)	2,33 mg/kg
Octabenzene CAS: 1843-05-6 EC: 217-421-2	STP	1 mg/L	Fresh water	0,052 mg/L
	Soil	66,8 mg/kg	Marine water	0,005 mg/L
	Intermittent	0,52 mg/L	Sediment (Fresh water)	100 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	10 mg/kg
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	STP	200 mg/L	Fresh water	1,1 mg/L
	Soil	0,32 mg/kg	Marine water	0,11 mg/L
	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER
81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015 Revised: 28/02/2022 Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Table with 5 columns: Identification, STP, Non-applicable, Fresh water, 0,3026 mg/L. Rows include Barium dibenzoate and phenol with various exposure scenarios like Soil, Intermittent, and Oral.

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer.

B.- Respiratory protection

Table with 5 columns: Pictogram, PPE, Labelling, CEN Standard, Remarks. Row 1: Filter mask for gases and vapours, CE CAT III, EN 405:2002+A1:2010, Replace when there is a taste or smell of the contaminant inside the face mask.

C.- Specific protection for the hands

Table with 5 columns: Pictogram, PPE, Labelling, CEN Standard, Remarks. Row 1: NON-disposable chemical protective gloves, CE CAT III, EN ISO 374-1:2016+A1:2018, EN 16523-1:2015+A1:2018, EN 420:2004+A1:2010, The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Table with 5 columns: Pictogram, PPE, Labelling, CEN Standard, Remarks. Row 1: Face shield, CE CAT II, EN 166:2002, EN 167:2002, EN 168:2002, EN ISO 4007:2018, Clean daily and disinfect periodically according to the manufacturer's instructions.

E.- Body protection

Table with 5 columns: Pictogram, PPE, Labelling, CEN Standard, Remarks. Row 1: Disposable clothing for protection against chemical risks, CE CAT III, EN 1149-1,2,3, EN 13034:2005+A1:2009, EN ISO 13982-1:2004/A1:2010, EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994, For professional use only. Row 2: Safety footwear for protection against chemical risk, CE CAT III, EN ISO 13287:2013, EN ISO 20345:2011, EN 13832-1:2019, Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation





RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	80 % weight
V.O.C. density at 25 °C:	755,01 kg/m ³ (755,01 g/L)
Average carbon number:	4
Average molecular weight:	72,1 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Thixotropic
Colour:	According to the markings on the package
Odour:	Solvent
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	65 °C
Vapour pressure at 25 °C:	17927 Pa
Vapour pressure at 50 °C:	60472 Pa (60,47 kPa)
Evaporation rate at 25 °C:	Non-applicable *

Product description:

Density at 25 °C:	940 kg/m ³
Relative density at 25 °C:	≤0,94
Dynamic viscosity at 25 °C:	1000 cP
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>1500 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	Non-applicable *
Partition coefficient n-octanol/water 25 °C:	Non-applicable *
Solubility in water at 25 °C:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 7/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	-21 °C
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	204 °C (ASTM D3466-76)
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 25 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 8/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: tetrahydrofuran (2B); Polyvinyl chloride (3); Silicon dioxide (1 % < RCS < 10 %) (3); Mica (RCS < 1%) (1); phenol (3)
- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Silicon dioxide (1 % < RCS < 10 %) CAS: 7631-86-9 EC: 231-545-4	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	LD50 oral	3000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 9/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

**RENOLIT ALKORPLUS - PVC SEAM SEALER**
81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Octabenzene CAS: 1843-05-6 EC: 217-421-2	10000 mg/kg	Non-applicable	Rat
phenol CAS: 108-95-2 EC: 203-632-7	100 mg/kg	630 mg/kg	Rat
	630 mg/kg	Non-applicable	Rabbit
	Non-applicable	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	2160 mg/L (96 h)	Non-applicable	Pimephales promelas	Fish
	Non-applicable	Non-applicable		
	Non-applicable	Non-applicable		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	1300 mg/L (96 h)	2850 mg/L (24 h)	Lepomis macrochirus	Fish
	2850 mg/L (24 h)	53 mg/L (192 h)	Daphnia magna	Crustacean
	53 mg/L (192 h)		Microcystis aeruginosa	Algae
phenol CAS: 108-95-2 EC: 203-632-7	14 mg/L (96 h)	12 mg/L (24 h)	Leuciscus idus	Fish
	12 mg/L (24 h)	370 mg/L (96 h)	Daphnia magna	Crustacean
	370 mg/L (96 h)		Chlorella vulgaris	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Non-applicable	Non-applicable	100 mg/L	14 days
	Non-applicable	Non-applicable	% Biodegradable	100 %
	Non-applicable	Non-applicable	% Biodegradable	100 %
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	0,25 g O2/g	2,08 g O2/g	100 mg/L	28 days
	2,08 g O2/g	0,12	% Biodegradable	92 %
	0,12		% Biodegradable	92 %
phenol CAS: 108-95-2 EC: 203-632-7	1,68 g O2/g	2,33 g O2/g	100 mg/L	14 days
	2,33 g O2/g	0,72	% Biodegradable	85 %
	0,72		% Biodegradable	85 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	BCF	Pow Log
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	3	0.46
	0.46	Low
	Low	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	0.46	0.56
	0.56	Low
	Low	
phenol CAS: 108-95-2 EC: 203-632-7	17	1.48
	1.48	Low
	Low	

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 10/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER
81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015 Revised: 28/02/2022 Version: 12 (Replaced 11)

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
tetrahydrofuran CAS: 109-99-9 EC: 203-726-8	Koc	23	Henry	7,19 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,498E-2 N/m (25 °C)	Moist soil	Yes
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No
phenol CAS: 108-95-2 EC: 203-632-7	Koc	50	Henry	2,2E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	1,847E-2 N/m (231,01 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP15 Waste capable of exhibiting a hazardous property listed above not directly displayed by the original waste, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP7 Carcinogenic, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 **UN number:** UN1133
- 14.2 **UN proper shipping name:** ADHESIVES containing flammable liquid
- 14.3 **Transport hazard class(es):** 3
Labels: 3
- 14.4 **Packing group:** II
- 14.5 **Environmental hazards:** No
- 14.6 **Special precautions for user**
Special regulations: 640D
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 **Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 **UN number:** UN1133
- 14.2 **UN proper shipping name:** ADHESIVES containing flammable liquid
- 14.3 **Transport hazard class(es):** 3
Labels: 3
- 14.4 **Packing group:** II
- 14.5 **Marine pollutant:** No
- 14.6 **Special precautions for user**
Special regulations: Non-applicable
EmS Codes: F-E, S-D
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 **Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- 14.1 **UN number:** UN1133
- 14.2 **UN proper shipping name:** ADHESIVES containing flammable liquid
- 14.3 **Transport hazard class(es):** 3
Labels: 3
- 14.4 **Packing group:** II
- 14.5 **Environmental hazards:** No
- 14.6 **Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 **Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 12/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 15: REGULATORY INFORMATION (continued)

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- “whoopee” cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

‘For professional users only’.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
- Zinc dibenzoate (553-72-0)

Texts of the legislative phrases mentioned in section 2:

- H319: Causes serious eye irritation.
- H351: Suspected of causing cancer.
- H335: May cause respiratory irritation.
- H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 13/14



Rely on it.

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



RENOLIT ALKORPLUS - PVC SEAM SEALER 81028-81029-81032-81034-81035-81037-81039-81049-81050-81054

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H301 - Toxic if swallowed.
 Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
 Acute Tox. 4: H332 - Harmful if inhaled.
 Carc. 2: H351 - Suspected of causing cancer.
 Eye Dam. 1: H318 - Causes serious eye damage.
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
 Muta. 2: H341 - Suspected of causing genetic defects.
 Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
 Skin Sens. 1B: H317 - May cause an allergic skin reaction.
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).
 STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
 STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Eye Irrit. 2: Calculation method
 Carc. 2: Calculation method
 STOT SE 3: Calculation method
 Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Date of compilation: 28/12/2015

Revised: 28/02/2022

Version: 12 (Replaced 11)

Page 14/14

Document generated with Chemeter (www.siam-it.com)