



## TECHNICAL DATA SHEET

### RENOLIT ALKORPLUS ALIVE SEAM FINISH - Type 81025101 Prana, 81025102 Dhyana, 81021003 Chandra

#### Application:

Reinforcement of welded joints, T-borders and corners for RENOLIT ALKORPLAN Touch varnished waterproofing membranes.

#### Technical Data:

- Base: Solution of vinyl resins and acrylic in MEK (methyl ethyl ketone)
- Color: Variable
- Viscosity: Approx. 2.500 mPa·s
- Solid Content: Approx. 18-23 %
- Specific Density: Approx. 0,9 g/cm<sup>3</sup>
- Flash Point: < 21°C (Highly flammable liquid and vapors)
- Toxicity: Causes serious eye irritation. May cause drowsiness or dizziness.

#### Placement:

For swimming pool membranes. Use polyethylene bottle to apply a 3-5 mm wide sealing of seams. Protect it against frost. Dilute only with MEK or THF. SHAKE WELL BEFORE USE. Let dry for at least 2 hours before filling the swimming pool.

#### Packaging:

Metallic Cans of 900 g. Six cans in a box.

#### Shelf Life:

3 years.

**Consumption:**

Approx. 1 kg/100 m

**Caution:**

As it is flammable product, one must avoid closeness to fire, flames and sparks during its storage and usage, hence it is to be used in well-ventilated areas. Do not smoke during its application. Do not use the product at temperatures below 10°C. Causes serious eye irritation. May cause drowsiness or dizziness. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use foam or dry powder for extinction.

**Storage:**

Follow the instructions relating to inflammable products, refer to the text on the label and take into consideration the data given on the safety sheet, which is available on request.

**For more information:**

Read MSDS.